



### **GEOFLOOR Specification item**

All areas indicated in the enclosed plans must be paved with regenerated LDPE plates. The thickness of the base layer and the materials to be used, will be those established by the Works Department after assessing the nature of the substrate and the intended use of the flooring. The contractor must indicate to the Works Department the materials used for the various layers and their origin. The type, thickness, finish, colour and characteristics of the elements will be those established by the Works Department for the individual areas. The flooring will be made up of perforated plates in regenerated LDPE, type GEOFLOOR by GEOPLAST with dimensions of 50x50 cm, height 2.4 cm, with bayonet coupling and permeability equal to 95% of its surface. The flooring will be laid dry on a layer of sediment as indicated by the manufacturer, on a substrate composed of a mixture of lapillus, volcanic sands and specific soil for turf with thicknesses as indicated by the manufacturer. The sowing, fertilizing and then laying of the paving will be performed, followed by first irrigation.

**Geoplast Spa**

Via Martiri della Libertà, 6/8  
35010 GRANTORTO (PD)  
Italia

Geoplast@Geoplast.it  
Tel +39 049 9490289  
Fax +39 049 9494028

Capitale Sociale € 2.000.000,00 i.v.  
Cod. Fisc. - Part. IVA e Reg. Impr. PD n. 03285310284  
R.E.A. n. 300667

**Geoplast.it**