



SALVAVERDE A Specification item

All areas indicated in the enclosed plans must be paved with regenerated PEHD plates. The thickness of the base layer and the materials to be used, will be those established by the Works Department after assessing the nature of the substrate, the use of the flooring and the indications of the manufacturer. The contractor must inform the Works Department of the materials used for the various layers and their origin. The type, thickness, finish, colour and characteristics of the elements will be those established by the Works Department, for individual areas.

The flooring will be made up of perforated plates in regenerated PEHD, stable to UV rays such as GEOPLAST's SALVAVERDE type 58x58 cm, height 4 cm, overlap coupling, load capacity 350 t/m2 and permeability equal to 95% of its surface.

The flooring will be laid dry on a bedding layer as indicated by the manufacturer. If the open surfaces are to be grassed, they must be flush filled with a mixture of 50% volcanic sand and 50% specific soil for turf: the application of the mixture must be repeated after compaction and the first humidification to compensate for the natural loss of material. Sowing, fertilisation and first irrigation will then be carried out.

SALVAVERDE B Specification item

All areas indicated in the enclosed plans must be paved with regenerated PEHD plates. The thickness of the base layer and the materials to be used, will be those established by the Works Department after assessing the nature of the substrate, the use of the flooring and the indications of the manufacturer. The contractor must inform the Works Department of the materials used for the various layers and their origin. The type, thickness, finish, colour and characteristics of the elements will be those established by the Works Department, for individual areas.

The flooring will be made up of perforated plates in regenerated PEHD, stable to UV rays such as GEOPLAST's SALVAVERDE type 58x58 cm, height 4 cm, overlap coupling, load capacity 350 t/m2 and permeability equal to 95% of its surface.

The flooring will be laid dry on a bedding layer as indicated by the manufacturer. If the open surfaces are to be grassed, they must be flush filled with a mixture of 50% volcanic sand and 50% specific soil for turf: the application of the mixture must be repeated after compaction and the first humidification to compensate for the natural loss of material. Sowing, fertilisation and first irrigation will then be carried out.