


Rev. 00 06/2018

GRIPPER TENNIS ROUGH Technical data sheet

1. DESCRIPTION

GRIPPER TENNIS ROUGH' is the ideal product for the construction of tennis courts. Its size, equal to 12" x 12" (one square foot) allows you to quickly and accurately create the regulatory tennis courts and allows you to highlight with different colors the field and the outside of the field. The rough surface, thanks to the presence of micro truncated cone pyramids distributed on the tile, allows to slow down the speed of the ball and therefore allows a fast but slower play compared to concrete surfaces or similar surfaces.



2. TECHNICAL CHARACTERISTICS

Material	-	Recycled Polypropylene (PP) 97-99%
	-	Additives 1-3%
Standard colours	-	Royal Blue (RAL 5010) Leaf Green (RAL 6002) Traffic Red (RAL 3020)
Dimensions	cm	30.5x30.5x H1.2 (10.75 pz/m²) 12"X12"X H1/2"
Weight	kg	0.37 (± 10%)
UV Stabilization	-	yes
Surface finish	-	Perforated and rough
Hooking type	-	Fast with snap-fit
Flatness	mm	0.00
Punch resistance	kN/m²	530
Flexural strength	N	490
Impact strength (coefficient of refund)	-	0.6
Installation time	m²/h/worker	50
Place of production	-	Italy



Rev. 00 06/2018


3. PACKAGING AND TRANSPORT

Product code	-	FGRIPRX3030
Packing Size	cm	100 x 120 x H170
Packaging typology	-	Stacked and wrapped in plastic film on pallets
Quantity per pallet	pcs	1500
Surface area per pallet	m ²	140
Gross weight of the package	kg	572

4. LAYING METHOD

<u>Laying surface</u>: Gripper should preferably be laid on rigid flat surfaces with a smooth finish (concrete, asphalt, resins, flooring, etc.). Before installing Gripper, the surfaces must be cleaned of dirt, dust, oil, grease, adhesive residues and other foreign materials.

<u>Installation of Gripper</u>: the tile is laid by means of a snap-fit quick coupling. The laying direction is from bottom to top and from left to right, holding the hooks upwards and to the right. For faster installation, the 4 x 3 tile sheets can be hung directly (always following the direction of installation) and are supplied already hung up and stacked on the pallets. When laying outside, leave an expansion joint near the curbs and any other object that may hinder thermal expansion. The space for expansion depends on the size of the playing field, but we recommend at least 5/10cm.



<u>Execution of the cut-off lines</u>: perfectly clean the surface of the floor made with Gripper. The lines must be made with normal street paint, first delimiting the lines with paper tape and then marking them with paint, finally removing the tape when work is completed.

<u>Cleaning</u>: Gripper can be cleaned like a normal smooth sports surface, with water, non-aggressive cleaning agents, vacuum cleaners, brushes, etc.